

DIVERTER STEM REPLACEMENT FOR LEDGE OR WALL MOUNTED GARDEN TUBS

Refer to the [Parts Breakdown Book](#) for replacement part numbers or [contact customer support](#) for help in finding a part

You may need several of these tools:

- Allen wrench (5/16 or 7/32)
- Channel locks
- » Crescent wrench
- » Flathead screwdriver
- » Phillips head screwdriver
- Pipe joint compound
- Soft cloth
- Teflon tape
- No tools necessary

Part key:

- | No. | Description |
|-----|-----------------------------------|
| 1 | Index Button |
| 2 | Handle Screw |
| 3 | Handle |
| 4 | Flange |
| 5 | Diverter stem and bonnet assembly |

1. Using a flathead screwdriver or knife, lift off index button, remove handle screw using a phillips head screwdriver, remove handle
2. Remove wall flange by turning counterclockwise.
3. Using a crescent wrench, turn the diverter stem and bonnet assembly counterclockwise to remove.
4. Insert new stem and bonnet assembly into diverter chamber and tighten with crescent wrench.

NOTE: CROSS THREADING OR OVER TIGHTENING WILL STRIP THE THREADS IN THE FAUCET BODY AND THE FAUCET WILL HAVE TO BE REPLACED

5. Replace wall flange and handle.
6. Turn handle to the right until it stops and insert arrow index button with arrow pointing toward spout.
7. Turn on water, check for proper operation.

